

- 26mm height
- 3 year Warranty
- Peak Load capable
- Light weight
- Output 1 isolated from outputs 2 & 3

MTW Series

15W to 60W Low Profile Triple Output Power Supplies

Key Market Segments & Applications

- Factory Automation
- Test & Measurement
- Automated Service
- Portable Equipment

MTW Features and Benefits

Features

- Low Profile
- Three Year Warranty
- Output 1 is isolated from outputs 2 & 3

Benefits

- Assists System Integration
- Low Cost of Ownership
- Outputs V2 & V3 can be connected in series

Specifications

ITEMS	MODELS		MTW15-51212	MTW30-51212	MTW60-51212
			MTW15-51515	MTW30-51515	MTW60-51515
Input Voltage Range		V	85 - 265VAC (47 - 440Hz)		
Input Current Typ	(1)	A	0.42 / 0.25	0.8 / 0.4	1.4 / 0.8
Inrush Current	(1)	A	25 / 50	20 / 40	20 / 40
Leakage Current (240VAC, 60Hz)		mA	0.75mA Max		
Max Output Power		W	16	30	60
			17.5	33	62.5
Efficiency (Typ)		%	71	76	76
Hold Up Time	(1)	ms	20 / 150	20 / 140	10 / 20
Output Voltage Adjustment		-	Fixed		
Overcurrent Protection		-	Yes, automatic recovery. Hiccup style on MTW30 & 60		
Overvoltage Protection		V	V1: Zener Clamp	V1: Zener Clamp	V1 & V2: Zener Clamp
Operating Temperature		-	-20°C start up. -10°C to +60°C, derating linearly to 70% load above 50°C		
Storage Temperature		-	-30°C to +75°C		
Humidity (Non condensing)		-	10 - 90%RH (Operating & storage) at 35°C		
Cooling		-	Convection		
Withstand Voltage		-	Input to ground 2kVAC, Input to output 3kVAC, Output to ground 500VAC		
Vibration (non operating)		-	5 - 10Hz: 10mm amplitude, 10 - 200Hz: 2G (19.6m/s ²)10m sweep time, 3 axis, 1 hour each		
Shock		-	Acceleration: 60G (588m/s ²) Half sine wave, 6 - 16ms pulse duration, 3x each direction		
Safety Agency Approvals		-	UL60950-1, CSA C22.2 No 60950-1 (C-UL), EN60950-1		
Immunity		-	EN61000-4-2 (Lv 4), -3, -4 (Lv 3), -5 (Lv 4), -6 (Lv 3), -8 (Lv 4), -11		
Conducted EMI		-	FCC-Class B, EN55011-B, EN55022-B		
Weight (Typ)		g	150	210	330
Size (WxHxL)		mm	50 x 26 x 127	65 x 26 x 140	83 x 26 x 185
Warranty		yrs	3		


Notes:

(1) 100/240VAC

Model Selector							
Model	Output	Voltage (V)	Regulation	Minimum Current (A)	Maximum Current (A)	Peak Current (A)	Ripple & Noise (mV)
MTW15-51212	V1	5V	4.75 - 5.25V	0	2.0	3.0	120
	V2	12V	11.4 - 12.6V	0	0.3	0.6	150
	V3	-12V	11.4 - 12.6V	0	0.2	0.3	150
MTW15-51515	V1	5V	4.75 - 5.25V	0	2.0	3.0	120
	V2	15V	14.4 - 15.6V	0	0.3	0.6	150
	V3	-15V	14.4 - 15.6V	0	0.2	0.3	150
MTW30-51212	V1	5V	4.9 - 5.3V	0	3	4.5	120
	V2	12V	11.4 - 12.6V	0	1.2	2.0	150
	V3	-12V	11.4 - 12.6V	0	0.3	0.45	150
MTW30-51515	V1	5V	4.9 - 5.3V	0	3	4.5	120
	V2	15V	14.25 - 15.75V	0	0.8	2.0	150
	V3	-15V	14.25 - 15.75V	0	0.3	0.45	150
MTW60-51212	V1	5V	4.9 - 5.3V	0	5.0	7.0	120
	V2	12V	11.4 - 12.6V	0	2.5	3.5	150
	V3	-12V	11.4 - 12.6V	0	0.5	0.7	150
MTW60-1515	V1	5V	4.9 - 5.3V	0	5.0	7.0	120
	V2	15V	14.25 - 15.75V	0	2.0	3.5	150
	V3	-15V	14.25 - 15.75V	0	0.5	0.7	150

Mating Connectors			
	Model	Input	Output
Connectors	MTW15	B3P5-VH-B	B8B-XH-2
JST	MTW30	B3P5-VH-B	B6P-VH-B
	MTW60	B3P5-VH-B	B8P-VH-B

Outline Drawing MTW15 Series



Outline Drawing MTW30 Series

